

RACK & PINION JACKS 1.5T TO 10T



Rack & pinion jack for easy and secure lifting, lowering, adjusting, etc. in all kinds of applications

- Self locking crank, keeps the load in the required position
- Easy and effective operation through optimal gear ratio
- For pulling or pushing
- Load: 1.5 - 10 tonnes
- Special versions on request
 - Different rack lengths
 - Different lift heights
 - Drive shaft connected to several jacks together
 - With internal brake and removable crank
- Available in:
 - Simple rack and pinion jack
 - With bracket for wall mounting
 - With bracket and extended shaft

Product type 1624	Product type 1685	Capacity	Version	Rack length	Lift	Lift/crank turn
205 186	205 195	1.5 t	Pulling version	1350 mm	800 mm	13.9 mm
205 187	205 196	1.5 t	Pulling version	1805 mm	1250 mm	13.9 mm
205 188	205 197	1.5 t	Pulling version	2055 mm	1500 mm	13.9 mm
205 189	205 198	1.5 t	Pulling version	2355 mm	1800 mm	13.9 mm
205 285	207 685	1.5 t	Pushing version	950 mm	400 mm	13.9 mm
205 190	205 199	1.5 t	Pushing version	1350 mm	800 mm	13.9 mm
205 192	205 200	1.5 t	Pushing version	1805 mm	1250 mm	13.9 mm
205 193	205 201	1 t	Pushing version	2055 mm	1500 mm	13.9 mm
205 194	205 202	0.75 t	Pushing version	2355 mm	1800 mm	13.9 mm
205 203	205 209	3 t	Pulling version	1350 mm	800 mm	8.0 mm
205 204	205 210	3 t	Pulling version	1800 mm	1250 mm	8.0 mm
205 205	205 211	3 t	Pulling version	2350 mm	1800 mm	8.0 mm
205 286	210 356	3 t	Pushing version	950 mm	400 mm	8.0 mm
205 206	205 212	3 t	Pushing version	1350 mm	800 mm	8.0 mm
205 207	205 213	2.5 t	Pushing version	1800 mm	1250 mm	8.0 mm
205 208	205 214	1 t	Pushing version	2350 mm	1800 mm	8.0 mm
205 215	205 288	5 t	Pulling version	1405 mm	800 mm	3.9 mm
205 216	205 289	5 t	Pulling version	2400 mm	1800 mm	3.9 mm
205 287	210 669	5 t	Pushing version	1000 mm	400 mm	3.9 mm
205 217	205 290	5 t	Pushing version	1405 mm	800 mm	3.9 mm
205 218	205 291	3 t	Pushing version	2400 mm	1800 mm	3.9 mm
200 065	200 073	10 t	Pulling version	1450 mm	800 mm	4.0 mm
200 066	200 074	10 t	Pushing version	1450 mm	800 mm	4.0 mm



Standard rack & pinion jack

Jack with extended crank shaft

DIMENSIONS (mm)

Capacity	f	g	h	ij	k	l	n	o	p	t	u	v	w	x	z
1.5 t	20.5	35	25	195	200	260	400	43.5	270	33.5	125	78	78	67	42.5
3 t	22.5	45	30	303	142	210	410	53	260	39.5	204	89	89	77	86
5 t	26	50	40	308	163	184	420	69.5	260	51	189	104	104	88	109
10 t	31	60	50	396	125	199	430	49	255	62.5	250	132	132	104	150.5

